



Only to be used with PAHZ 8 Series Chassis

## 53 ft. 110 in. Container

▶ **Steel Construction**

▶ **PACU 880001-882200** ▶ **PACU 882201-895001**

features lower-profile ceiling supports

**outside dimensions**

length width height  
53' 0" 8' 6" 9' 6 1/2"

**inside dimensions**

length width  
52' 6" 8' 2 5/8"

**door opening**

height width height  
9' 1 3/8" 8' 2 1/4" 9' 1 3/8"

**cubic capacity**

cu ft  
3,947

**maximum design**

**payload weight\*** lbs  
56,890

**tare weight**

lbs  
10,310

**maximum design**

**gross weight** lbs  
67,200

**floor rating**

forklift front axle  
24,000

**side**

**vents**  
yes

**tie**

**downs**  
no



## 53 ft. Container

▶ **Steel Construction**

▶ **PATU 544625-545324**

**outside dimensions**

length width height  
53' 0" 8' 6" 9' 6 1/2"

**inside dimensions**

length width  
52' 5 11/16" 8' 2"

**door opening**

height width height  
8' 11 3/8" 8' 2" 8' 11"

**cubic capacity**

cu ft  
3,857

**maximum design**

**payload weight\*** lbs  
56,600

**tare weight**

lbs  
10,600

**maximum design**

**gross weight** lbs  
67,200

**floor rating**

forklift front axle  
24,000

**side**

**vents**  
yes

**tie**

**downs**  
yes



## 53 ft. Container

▶ **Steel Construction**

▶ **PATU 540000-544624**

**outside dimensions**

length width height  
53' 0" 8' 6" 9' 6 1/2"

**inside dimensions**

length width  
52' 5 11/16" 8' 2"

**door opening**

height width height  
8' 11 3/8" 8' 2" 8' 11"

**cubic capacity**

cu ft  
3,857

**maximum design**

**payload weight\*** lbs  
56,310

**tare weight**

lbs  
10,890

**maximum design**

**gross weight** lbs  
67,200

**floor rating**

forklift front axle  
20,000

**side**

**vents**  
yes

**tie**

**downs**  
yes



## 53 ft. Container

▶ **Steel Construction**

▶ **APCU 537501-539500**

**outside dimensions**

length width height  
53' 0" 8' 6" 9' 6 1/2"

**inside dimensions**

length width  
52' 5 11/16" 8' 2 5/8"

**door opening**

height width height  
8' 11 5/16" 8' 2" 8' 10"

**cubic capacity**

cu ft  
3,857

**maximum design**

**payload weight\*** lbs  
56,090

**tare weight**

lbs  
11,110

**maximum design**

**gross weight** lbs  
67,200

**floor rating**

forklift front axle  
12,000

**side**

**vents**  
yes

**tie**

**downs**  
no

\*Maximum legal payload weight will vary depending on chassis weight and applicable federal, state and local laws.



## 53 ft. Container

▶ Aluminum Construction ▶ APCU 530495-537499

### outside dimensions

length	width	height
53' 0"	8' 6"	9' 6 1/2"

### inside dimensions

length	width
52' 6 1/2"	8' 3"

### door opening

height	width	height
8' 11"	8' 2"	8' 11"

### cubic capacity

cu ft  
3,864

### maximum design

payload weight\* lbs  
57,600

### tare weight

lbs  
9,600

### maximum design

gross weight lbs  
67,200

### floor rating

forklift front axle  
12,000

### side

vents  
no

### tie

downs  
no



## 48 ft. Container

▶ Steel Construction ▶ PATU 440000-441099

### outside dimensions

length	width	height
48' 0"	8' 6"	9' 6 1/2"

### inside dimensions

length	width
47' 5 11/16"	8' 2 5/8"

### door opening

height	width	height
8' 11 5/16"	8' 2"	8' 10 5/16"

### cubic capacity

cu ft  
3,489

### maximum design

payload weight\* lbs  
57,280

### tare weight

lbs  
9,920

### maximum design

gross weight lbs  
67,200

### floor rating

forklift front axle  
24,000

### side

vents  
yes

### tie

downs  
no



## 48 ft. Container

▶ Aluminum Construction ▶ APLU 489043-493235

### outside dimensions

length	width	height
48' 0"	8' 6"	9' 6 1/2"

### inside dimensions

length	width
47' 6"	8' 2 1/2"

### door opening

height	width	height
8' 11"	8' 2 1/4"	8' 11"

### cubic capacity

cu ft  
3,474

### maximum design

payload weight\* lbs  
58,650

### tare weight

lbs  
8,550

### maximum design

gross weight lbs  
67,200

### floor rating

forklift front axle  
12,000

### side

vents  
no

### tie

downs  
no



## 48 ft. Container

▶ Steel Construction / ISO

▶ APLU 486783-488000 ▶ APLU 496000-497590

### outside dimensions

length	width	height
48' 0"	8' 6"	9' 6 1/2"

### inside dimensions

length	width
47' 5 11/16"	8' 2 1/2"

### door opening

height	width	height
8' 11"	8' 2"	8' 10"

### cubic capacity

cu ft  
3,454

### maximum design

payload weight\* lbs  
56,350

### tare weight

lbs  
10,850

### maximum design

gross weight lbs  
67,200

### floor rating

forklift front axle  
12,000

### side

vents  
yes

### tie

downs  
yes

\*Maximum legal payload weight will vary depending on chassis weight and applicable federal, state and local laws.



## 45 ft. Container

► Steel Construction / ISO

### outside dimensions

length	width	height
45' 0"	8' 0"	9' 6"

### inside dimensions

length	width
44' 5 23/32"	7' 8 19/32"

### door opening

height	width	height
8' 10 13/32"	7' 8 1/8"	8' 6 5/32"

### cubic capacity

cu ft  
3,038

### maximum design

payload weight\* lbs  
62,600

### tare weight

lbs  
10,200

### maximum design

gross weight lbs  
72,800

### floor rating

forklift front axle  
12,000

### side

vents  
yes

### tie

downs  
yes



## 40 ft. High Cube Container

► Steel Construction / ISO

### outside dimensions

length	width	height
40' 0"	8' 0"	9' 6"

### inside dimensions

length	width
39' 5 11/16"	7' 8 1/2"

### door opening

height	width	height
8' 10 3/16"	7' 8 5/16"	8' 5 11/16"

### cubic capacity

cu ft  
2,693

### maximum design

payload weight\* lbs  
58,600

### tare weight

lbs  
8,600

### maximum design

gross weight lbs  
67,200

### floor rating

forklift front axle  
12,000

### side

vents  
yes

### tie

downs  
yes



## 40 ft. Container

► Steel Construction / ISO

### outside dimensions

length	width	height
40' 0"	8' 0"	8' 6"

### inside dimensions

length	width
39' 5 11/16"	7' 8 1/2"

### door opening

height	width	height
7' 10 3/16"	7' 8 5/16"	7' 5 11/16"

### cubic capacity

cu ft  
2,389

### maximum design

payload weight\* lbs  
59,000

### tare weight

lbs  
8,200

### maximum design

gross weight lbs  
67,200

### floor rating

forklift front axle  
12,000

### side

vents  
yes

### tie

downs  
yes



## 20 ft. Container

► Steel Construction / ISO

### outside dimensions

length	width	height
19' 10 1/2"	8' 0"	8' 6"

### inside dimensions

length	width
19' 4 1/4"	7' 8 1/2"

### door opening

height	width	height
7' 10 5/16"	7' 8 3/16"	7' 5 11/16"

### cubic capacity

cu ft  
1,172

### maximum design

payload weight\* lbs  
48,020

### tare weight

lbs  
4,890

### maximum design

gross weight lbs  
52,910

### floor rating

forklift front axle  
12,000

### side

vents  
yes

### tie

downs  
yes

\*Maximum legal payload weight will vary depending on chassis weight and applicable federal, state and local laws.



Only to be used with PACU 8 Series Container

## 53 ft. 110 in. Fixed Chassis

▶ Low-Profile G/Neck ▶ PAHZ 805001-815550

**dimensions**

length width height  
53' 8" 8' 0" 4' 0"

**tare weight**

lbs  
7,450

**tandem  
location**

54"-150"

**kingpin  
location**

36"

**landing gear  
location**

94"



## 53 ft. Fixed Chassis

▶ PATZ 500000-504889

**dimensions**

length width height  
53' 8" 8' 0" 4' 0"

**tare weight**

lbs  
7,450

**tandem  
location**

54"-150"

**kingpin  
location**

36"

**landing gear  
location**

94"



## 40 ft. Fixed Chassis

**dimensions**

length width height  
40' 8" 8' 0" 4' 0"

**tare weight**

lbs  
6,500

**tandem  
location**

54"

**kingpin  
location**

30"

**landing gear  
location**

94"



## 20 ft. Slider Chassis

**dimensions**

length width height  
23' 8" 8' 0" 4' 0"

**tare weight**

lbs  
6,600

**tandem  
location**

54"

**kingpin  
location**

18"

**landing gear  
location**

84"

\*Maximum legal payload weight will vary depending on chassis weight and applicable federal, state and local laws.



## 45, 48, 53 ft. Extendable Chassis

- ▶ APLZ195001-199299 ▶ APLZ 543863-544561
- ▶ APLZ 581802-582381 ▶ PATZ 530000-531546

### 45 ft. dimensions

length width height  
45' 8" 8' 0" 4' 0"

### tare weight

lbs  
7,750-8,500

### tandem location

54"-144"

### kingpin location

36"

### landing gear location

94"

### 48 ft. dimensions

length width height  
48' 8" 8' 0" 4' 0"

### tare weight

lbs  
7,750-8,500

### tandem location

54"-144"

### kingpin location

36"

### landing gear location

94"

### 53 ft. dimensions

length width height  
53' 8" 8' 0" 4' 0"

### tare weight

lbs  
7,750-8,500

### tandem location

54"-144"

### kingpin location

36"

### landing gear location

94"



## 40, 45, 48 ft. Extendable Chassis

- ▶ APLZ 130001-187819 ▶ GCEZ 452071-695746
- ▶ PATZ 130405-695258

### 40 ft. dimensions

length width height  
40' 8" 8' 0" 4' 0"

### tare weight

lbs  
7,230-8,400

### tandem location

54"-108"

### kingpin location

36"

### landing gear location

94"

### 45 ft. dimensions

length width height  
45' 8" 8' 0" 4' 0"

### tare weight

lbs  
7,230-8,400

### tandem location

54"-108"

### kingpin location

36"

### landing gear location

94"

### 48 ft. dimensions

length width height  
48' 8" 8' 0" 4' 0"

### tare weight

lbs  
7,230-8,400

### tandem location

54"-108"

### kingpin location

36"

### landing gear location

94"